

**Commonwealth of Kentucky
Environmental and Public Protection Cabinet
Department for Environmental Protection
Division for Air Quality
803 Schenkel Lane
Frankfort, Kentucky 40601
(502) 573-3382**

**AIR QUALITY PERMIT
Issued under 401 KAR 52:040**

Permittee Name: James Ritter Lumber Co.
Mailing Address: P.O. Box 10, Summer Shade, KY 42166

Source Name: James Ritter Lumber Co.
Mailing Address: P.O. Box 10
Summer Shade, KY 42166


Source Location: 4796 Summer Shade Rd

Permit ID: S-07-144
Agency Interest #: 6165
Activity ID: APE20070001
Review Type: Minor Source, Construction / Operating
Source ID: 21-169-00014

Regional Office: Bowling Green Regional Office
1508 Westen Avenue
Bowling Green, KY 42104
(270) 746-7475

County: Metcalfe

Application
Complete Date: December 5, 2007
Issuance Date: December 13, 2007
Revision Date:
Expiration Date: December 13, 2017

E-signed by John S. Lyons


**John S. Lyons, Director
Division for Air Quality**

SECTION A - PERMIT AUTHORIZATION

Pursuant to a duly submitted application the Kentucky Division for Air Quality hereby authorizes the operation of the equipment described herein in accordance with the terms and conditions of this permit. This permit has been issued under the provisions of Kentucky Revised Statutes Chapter 224 and regulations promulgated pursuant thereto.

The permittee shall not construct, reconstruct, or modify any affected facilities without first submitting a complete application and receiving a permit for the planned activity from the permitting authority, except as provided in this permit or in 401 KAR 52:040, State-origin permits.

Issuance of this permit does not relieve the permittee from the responsibility of obtaining other permits, licenses, or approvals that may be required by the Cabinet or other federal, state, or local agencies.

SECTION B - EMISSION POINTS, EMISSION UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS

Emission Unit 01 Wood Fired Boiler

Description:

Model: AFS 300-15WF
Construction Date: Feb 2008
Fuel Input: 14.1 MMBtu/hr
Primary Fuel: wood residue
Controls: multiclone

APPLICABLE REGULATIONS:

- a. 401 KAR 59:015, New Indirect Heat Exchangers applicable to an emission unit with a capacity less than 250 MMBtu/hr and commenced on or after April 9, 1972
- b. 401 KAR 60:005, incorporating by reference 40 CFR 60, Subpart Dc, Standards of performance for small industrial-commercial-institutional steam generating units, applies to each steam generating unit commenced after June 8, 1989 that has a maximum design heat input capacity between 10 and 100 MMBtu/hr.

1. Operating Limitations:

None.

2. Emission Limitations:

- a. Pursuant to 401 KAR 59:015, Section 4(1)(c), particulate emissions shall not exceed 0.52 lb/MMBtu, based on a three-hour average.
- b. Pursuant to 401 KAR 59:015, Section 4(2), emissions shall not exceed 20 percent opacity based on a six-minute average, except:
 - (i.) That a maximum of 40 percent opacity shall be permissible for not more than 6 consecutive minutes in any 60 consecutive minutes during cleaning the fire box or blowing soot.
 - (ii.) For emission from an indirect heat exchanger during building a new fire for the period required to bring the boiler up to operating conditions provided the method used is that recommended by the manufacturer and the time does not exceed the manufacturer's recommendations.
- c. Pursuant to 401 KAR 59:015, Section 5(1)(c), sulfur dioxide emission shall not exceed 4.68 lb/MMBtu based on a twenty-four-hour average.

SECTION B - EMISSION POINTS, EMISSION UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

3. Testing Requirements:

See General Conditions, Section C.7.

4. Monitoring Requirements:

- a. Pursuant to 401 KAR 52:040, Section 23, the permittee shall monitor the amount of fuel burned and hours of operation on a monthly basis.
- b. Pursuant to 401 KAR 52:040, Section 23, the permittee shall perform a qualitative visible observation of the opacity emissions from the stack on a weekly basis and maintain a log of the observations. If visible emissions from the stack are seen, then the opacity shall be determined using EPA Reference Method 9 and if the opacity reading is greater than twenty (20) percent, then initiate an inspection of the equipment for any repairs.

5. Recordkeeping Requirements:

Pursuant to 401 KAR 52:040, Section 23, the permittee shall record fuel usage and hours of operation on a monthly basis.

6. Reporting Requirements:

See Section C (3).

7. Control Equipment:

- a. The multiclone flyash collector shall be operated to maintain compliance with permitted emissions limitations in accordance with manufacturer's specifications and/or standard operating practices.
- b. Records regarding the maintenance of the multiclone shall be maintained.

SECTION C - GENERAL CONDITIONS

1. Administrative Requirements

- a. The permittee shall comply with all conditions of this permit. Noncompliance shall be a violation of 401 KAR 52:040, Section 3(1)(b) and is grounds for enforcement action including but not limited to the termination, revocation and reissuance, or revision of this permit.
- b. This permit shall remain in effect for a fixed term of ten (10) years following the original date of issue. Permit expiration shall terminate the source's right to operate unless a timely and complete renewal application has been submitted to the Division at least six months prior to the expiration date of the permit. Upon a timely and complete submittal, the authorization to operate within the terms and conditions of this permit, including any permit shield, shall remain in effect beyond the expiration date, until the renewal permit is issued or denied by the Division. [401 KAR 52:040, Section 15]
- c. Any condition or portion of this permit which becomes suspended or is ruled invalid as a result of any legal or other action shall not invalidate any other portion or condition of this permit [Section 1a-11 of the *Cabinet Provisions and Procedures for Issuing State-Origin Permits* incorporated by reference in 401 KAR 52:040 Section 23].
- d. Pursuant to materials incorporated by reference by 401 KAR 52:040, this permit may be revised, revoked, reopened, reissued, or terminated for cause. The filing of a request by the permittee for any permit revision, revocation, reissuance, or termination, or of a notification of a planned change or anticipated noncompliance shall not stay any permit condition [Section 1a-4, 5, of the *Cabinet Provisions and Procedures for Issuing State-Origin Permits* incorporated by reference in 401 KAR 52:040 Section 23].
- e. This permit does not convey property rights or exclusive privileges [Section 1a-8 of the *Cabinet Provisions and Procedures for Issuing State-Origin Permits* incorporated by reference in 401 KAR 52:040 Section 23].
- f. Nothing in this permit shall alter or affect the liability of the permittee for any violation of applicable requirements prior to or at the time of permit issuance [401 KAR 52:040 Section 11(3)].
- g. This permit shall be subject to suspension at any time the permittee fails to pay all fees within 90 days after notification as specified in 401 KAR 50:038, Air emissions fee.

SECTION C - GENERAL CONDITIONS (CONTINUED)**3. Reporting Requirements**

- a. (1) In accordance with the provisions of 401 KAR 50:055, Section 1, the permittee shall notify the Regional Office listed on the front of this permit concerning startups, shutdowns, or malfunctions as follows:
 - i. When emissions during any planned shutdowns and ensuing startups will exceed the standards, notification shall be made no later than three (3) days before the planned shutdown, or immediately following the decision to shut down, if the shutdown is due to events which could not have been foreseen three (3) days before the shutdown.
 - ii. When emissions due to malfunctions, unplanned shutdowns and ensuing startups are or may be in excess of the standards, notification shall be made as promptly as possible by telephone (or other electronic media) and shall be submitted in writing upon request.
- (2) The permittee shall promptly report deviations from permit requirements including those attributed to upset conditions (other than emission exceedances covered by Reporting Requirement condition a.(1) above), the probable cause of the deviation, and corrective or preventive measures taken; to the Regional Office listed on the front of this permit within 30 days. Other deviations from permit requirements shall be included in the semiannual report [Section 1b-V-3 of the *Cabinet Provisions and Procedures for Issuing State-Origin Permits* incorporated by reference in 401 KAR 52:040 Section 23].
- b. The permittee shall furnish information requested by the Cabinet to determine if cause exists for modifying, revoking and reissuing, or terminating the permit; or to determine compliance with the permit [Section 1a-6 of the *Cabinet Provisions and Procedures for Issuing State-Origin Permits* incorporated by reference in 401 KAR 52:040 Section 23].

4. Inspections

In accordance with the requirements of 401 KAR 52:040, Section 3(1)(f) the permittee shall allow authorized representatives of the Cabinet to perform the following during reasonable times. Reasonable times are defined as during all hours of operation, during normal office hours; or during an emergency:

- a. Enter upon the premises to inspect any facility, equipment (including air pollution control equipment), practice, or operation.
- b. To access and copy any records required by the permit.
- c. Inspect, at reasonable times, any facilities, equipment (including monitoring and pollution control equipment), practices, or operations required by the permit.
- d. Sample or monitor, at reasonable times, substances or parameters to assure compliance with the permit or any applicable requirements.

SECTION C - GENERAL CONDITIONS (CONTINUED)**5. Emergencies/Enforcement Provisions**

- a. The permittee shall not use as defense in an enforcement action, the contention that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance [Section 1a-3 of the *Cabinet Provisions and Procedures for Issuing State-Origin Permits* incorporated by reference in 401 KAR 52:040 Section 23].
- b. An emergency shall constitute an affirmative defense to an action brought for the noncompliance with the technology-based emission limitations if the permittee demonstrates through properly signed contemporaneous operating logs or relevant evidence that:
 - (1) An emergency occurred and the permittee can identify the cause of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During an emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements in the permit; and
 - (4) The permittee notified the Division as promptly as possible and submitted written notice of the emergency to the Division within two working days after the time when emission limitations were exceeded due to the emergency and included a description of the emergency, steps taken to mitigate emissions, and corrective actions taken.
- c. Emergency provisions listed in General Condition 5.b are in addition to any emergency or upset provision contained in an applicable requirement [401 KAR 52:040, Section 22(1)].
- d. In an enforcement proceeding, the permittee seeking to establish the occurrence of an emergency shall have the burden of proof. [401 KAR 52:040, Section 22(2)].

6. Compliance

- a. For the purpose of demonstration of continuing compliance, the following guidelines shall be followed:
 - (1) Pursuant to 401 KAR 50:055, General compliance requirements, Section 2(5), all air pollution control equipment and all pollution control measures proposed by the application in response to which this permit is issued shall be in place, properly maintained, and in operation at any time an affected facility for which the equipment and measures are designed is operated, except as provided by 401 KAR 50:055, Section 1.
 - (2) All the air pollution control systems shall be maintained regularly in accordance with good engineering practices and the recommendations of the respective manufacturers. A log shall be kept of all routine and nonroutine maintenance performed on each control device. Daily observations are required during daylight hours of all operations, control equipment and any visible emissions to determine whether conditions appear to be either normal or abnormal. If the operations, controls and/or emissions appear to be abnormal, the permittee must then comply with the requirements of Section C – General Conditions, 3.a.(2), of this permit.
- b. Pursuant to 401 KAR 52:040, Section 19, the permittee shall certify compliance with the terms and conditions contained in this permit by January 30th of each year, by completing and returning a Compliance Certification Form (DEP 7007CC) (or an approved alternative)

SECTION C - GENERAL CONDITIONS (CONTINUED)

to the Regional Office listed on the front of this permit in accordance with the following requirements:

- (1) Identification of the term or condition;
- (2) Compliance status of each term or condition of the permit;
- (3) Whether compliance was continuous or intermittent;
- (4) The method used for determining the compliance status for the source, currently and over the reporting period, and
- (5) For an emissions unit that was still under construction or which has not commenced operation at the end of the 12-month period covered by the annual compliance certification, the permittee shall indicate that the unit is under construction and that compliance with any applicable requirements will be demonstrated within the timeframes specified in the permit.

7. Construction Requirements:

Pursuant to a duly submitted application the Kentucky Division for Air Quality hereby authorizes the construction of the equipment described herein, in accordance with the terms and conditions of this permit.

- a. Pursuant to 401 KAR 52:040, Section 12(3), unless construction is commenced on or before 18 months after the date of issuance of this permit, or if construction is commenced and then stopped for any consecutive period of 18 months or more, or is not completed within a reasonable timeframe, then the construction and operating authority granted by this permit for those affected facilities for which construction was not completed shall immediately become invalid. Upon a written request, the Cabinet may extend these time periods if the source shows good cause.
- b. Pursuant to 401 KAR 52:040, Section 12(4)(a) and 401 KAR 59:005, General provisions, Section 3(1), within 30 days following construction commencement, within 15 days following start-up and attainment of maximum production rate, or within 15 days following the issuance date of this permit, whichever is later, the owner and/or operator of the affected facilities specified on this permit shall furnish to the Regional Office listed on the front of this permit, with a copy to the Division's Frankfort Central Office, the following:
 - (1) Date when construction commenced.
 - (2) Start-up date of each of the affected facilities listed on this permit.
 - (3) Date when maximum production rate was achieved.
- c.
 - (1) Pursuant to 401 KAR 59:005, General provisions, Section 3(1)(b), unless notification and justification to the contrary are received by this Division, the date of achieving the maximum production rate at which the affected facilities will be operated shall be deemed to be 30 days after initial start-up.
 - (2) Pursuant to 401 KAR 59:005, General provisions, Section 3(1)(b), unless notification and justification to the contrary are received by this Division, the date of achieving the maximum production rate at which the affected facilities will be operated shall be deemed to be 30 days after initial start-up.

SECTION C - GENERAL CONDITIONS (CONTINUED)

- (3) Pursuant to 401 KAR 50:045, Section 2, a source required to conduct a performance test shall submit a completed Compliance Test Protocol form, DEP form 6028, or a test protocol a source has developed for submission to other regulatory agencies, in a format approved by the cabinet, to the Division's Frankfort Central Office a minimum of sixty (60) days prior to the scheduled test date. Pursuant to 401 KAR 50:045, Section 7, the Division shall be notified of the actual test date at least Thirty (30) days prior to the test.
 - (4) Pursuant to 401 KAR 50:045 Section 5 in order to demonstrate that a source is capable of complying with a standard at all times, a performance test shall be conducted under normal conditions that are representative of the source's operations and create the highest rate of emissions. If [When] the maximum production rate represents a source's highest emissions rate and a performance test is conducted at less than the maximum production rate, a source shall be limited to a production rate of no greater than 110 percent of the average production rate during the performance tests. If and when the facility is capable of operation at the rate specified in the application, the source may retest to demonstrate compliance at the new production rate. The Division for Air Quality may waive this requirement on a case-by-case basis if the source demonstrates to the Division's satisfaction that the source is in compliance with all applicable requirements.
- d. Operation of the affected facilities authorized by this permit shall not commence until compliance with applicable standards specified herein has been demonstrated in accordance with the requirements of 401 KAR 52:040, Section 12(4)(b). Until compliance is demonstrated, the source may only operate for the purpose of demonstrating compliance.

SECTION D - INSIGNIFICANT ACTIVITIES

The following listed activities have been determined to be insignificant activities for this source pursuant to 401 KAR 52:040, Section 6. Although these activities are designated as insignificant the permittee must comply with the applicable regulation. Process and emission control equipment at each insignificant activity subject to an opacity standard shall be inspected monthly and a qualitative visible emissions evaluation made. Results of the inspection, evaluation, and any corrective action shall be recorded in a log.

<u>Description</u>	<u>Generally Applicable Regulation</u>
Wood Residue Storage	N/A